


**TIME ADJUSTMENT WORKSHEET - BUTTONS AS PRIMARY**

**LANE MALFUNCTION - TIME ADJUSTMENT**

EVENT:	HEAT:	ADJUSTED BY:
--------	-------	--------------

LANE	OFFICIAL BUTTON TIME (T <sub>B</sub> )	WATCH TIME (T <sub>w</sub> )	$\Delta = T_B - T_w$ [discard negative values and those greater than 0.3]	LANE ADJUSTMENT WORK AREA (T <sub>w</sub> + $\Delta a$ ) 	Adjusted official time for malfunction lane
1					
2					
3					
4					
5					
6					
7					
8					
9					
10					

**Sum of all valid differences  $\Sigma\Delta$**  


**Average difference  $\Delta a = \Sigma\Delta / N$**  

OFFICIAL BUTTON TIME is the middle button or average of 2 buttons or single button if no others are pushed. N = number of lanes with valid time

Note: Lane malfunction confirmed when all buttons of a lane failed or not pressed at finish  
Valid time delta are those greater than or equal to 0.0 and less than or equal to 0.30 second

**LANE MALFUNCTION - TIME ADJUSTMENT**

EVENT:	HEAT:	ADJUSTED BY:
--------	-------	--------------

LANE	OFFICIAL BUTTON TIME (T <sub>B</sub> )	WATCH TIME (T <sub>w</sub> )	$\Delta = T_B - T_w$ [discard negative values and those greater than 0.3]	LANE ADJUSTMENT WORK AREA (T <sub>w</sub> + $\Delta a$ ) 	Adjusted official time for malfunction lane
1					
2					
3					
4					
5					
6					
7					
8					
9					
10					

**Sum of all valid differences  $\Sigma\Delta$**  

**Average difference  $\Delta a = \Sigma\Delta / N$**  

OFFICIAL BUTTON TIME is the middle button or average of 2 buttons or single button if no others are pushed. N = number of lanes with valid time